

Today's Date: _____

Quote Due Date: _____

REPLACEMENT DOORS ONLY REQUEST FORM

 Customer: _____
 Contact: _____
 Phone: _____ Cell: _____
 Fax: _____
 E-mail: _____

 Job Name: _____
 Location: _____
 Required Ship Date: _____
 Shipping Address: _____

Standard Booking / Shipping Lead-Time: 2-3 Weeks
Quality Crating with Doors Packaged on end to keep Straight


Door Information

Entrance Allowable Information:

	Max Width	Max Height
Single Speed Side Opening	42"	96"
Two Speed Side Opening	84"	96"
Single Center Opening	50"	96"
Two Speed Center Opening	100"	96"



Required Information:



Door Skin Thickness:
 20 Ga 16 Ga

Sound Deadening Doors:
 Yes No

Non Standard Door Finish - Longer Lead Time:			COLOR
<input type="checkbox"/> #4 (316) SS	<input type="checkbox"/> #8 (304) SS	<input type="checkbox"/> 5SM RIMEX	<input type="checkbox"/> _____
Standard Door Finish Colors:			
<input type="checkbox"/> WHITE	<input type="checkbox"/> CREAM	<input type="checkbox"/> LIGHT IVORY	<input type="checkbox"/> ALLADIN BLUE
<input type="checkbox"/> BLACK	<input type="checkbox"/> AGATE GREY	<input type="checkbox"/> STONE GREY	<input type="checkbox"/> TARPULIN GREY

Entrance Doors (UL Labeled):


Door Hand	Door Speed	Opening Size	Landing Qty	Std. Door Finish	EM Key Layout
(left, right, center)	(1, 2)	(not panel size)	(not panel Qty)	(painted/primed, #4 (304) SS)	(KMO, Tri Lock, Plain)
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Cab Doors (NOT Labeled):

Door Hand	Door Speed	Opening Size	Opening Qty	Std. Door Finish	Door Thickness
(left, right, center)	(1, 2)	(not panel size)	(1, 2, 3)	(painted/primed, #4 (304) SS)	(varies)
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Door Construction Detail - (Entrance 1.25" Thickness Only) - (Cab Thickness Varies)

- 1) Entrance Doors 1.5" hour fire rating UL label - (Cab Doors NOT labeled)
- 2) Doors are hand specific and would have to be drilled out to accommodate being the opposite hand
- 3) Painted doors have no cladding as a standard (gloss paint will require a sheet steel skin)
- 4) Otherwise doors can be clad in 20ga. Stainless. (16ga. Optional)
- 5) Use (2) Nylube slide door guides (gibs) with (1) 14ga. Safety retainer gib (per door panel)
- 6) Drilled for GAL door operator. (Drawings required for any other door operator).
- 7) Sight guard finish matched door finish.



Standard Spec: Doors: 16 ga cold rolled steel construction with 14ga stiffeners painted black wrapped with 20 ga #4 stainless
 No Center Opening MEI doors are allowed in Canada at this time