

Todays Date:	
Quote Due Date:	

ENTRANCE QUOTE REQUEST FORM

Customer: Contact: Phone: Fax: E-mail:	Location: Required Ship Date: Shipping Address:		
Entrance Package Frame Construction (2" square profile)			
Full Package (Doors & Frames)	Doors Only Bolted (standa	rd) Welded and Mitered	
Capacity Class Code Total Travel Platform Width Clear Hoistway Width *MEI presumes platform is centered	Enamel (powder coated) #4 Stainless Steel #8 Stainless Steel #4 Bronze/Muntz		
in hoistway	Frame Material Thickness 16 Gauge (standard)	Door Operator By Others: GAL Drilling (standard)	
Door Information	14 Gauge *If Bronze/Muntz is specified above the	Other	
Front: Quantity Door Size: Width x Depth Door Type	frames will be wrapped in 18 Gauge	Additional Options Cut outs required in frames Fire Service	
Single Speed Two Speed Center Opening Two Speed Center Opening	Entrance Wall Material Gypsum CMU/Concrete Other	Access Other Jamb Braille by MEI Self Adhesive	
Rear Side Quantity Door Finish Enamel (powder coated) #4 Stainless Steel #8 Stainless Steel #4 Bronze/Muntz #8 Bronze/Muntz	*If wall materials and thickness are different at openings please specify each Sill Material (groutless design) Aluminum (standard) Nickel Silver	Pin Mount Stud Mount Keyholes - Entrance doors (KMO) What landings: Tri-Locks What landings: Sound Deadening Frames Yes No	
Other	Stainless Steel Bronze/Muntz	Doors Yes No	

Frames: Enamel - cold rolled A-1088, Stainless 304, Bronze/Muntz 60/40 wrapped 18ga
Doors: 16 ga cold rolled steel construction wrapped with 20 ga stainless or 18 ga Bronze/Muntz
Fascia: 14ga Galvanield -- Header: 12 ga steel enamel -- Struts: 10 ga steel enamel

Frames and Door: Bronze/M untz will be powdered clear coated with 20% gloss UL Ratings: All doors are UL rated, All frames with gypsum wall construction are UL rated

Standard Spec: